

	Top part type (S.H.I.S)	Bottom part type (S.H.I.S)	Fork steerer type	Upper bearing size (mm)	Bottom bearing size (mm)	Upper HT inside diam. (mm)	Bottom HT inside diam. (mm)	Stem clamp diam. (mm)	Crown race seat diam. (mm)	Top stack height (mm)	Bottom stack height (mm)	Weight (g)
Blink	IS42	IS52	tapered/ standard 1-1/8"	41.8x30.5x8	52x40x8	42	52.1	28.6	39.79/30.015	5.4	0	72
Prime	IS42	IS42	standard 1-1/8"	41.8x30.5x8	41.8x30.5x8	42	42	28.6	30.015	5.4	0	61
Flash	EC34	ZS49	standard 1-1/8"	41x30.15x7	41.8x30.5x8	33.95	49.61	28.6	30.015	12.7	2.8	109
Blaze	EC34	EC49	tapered/ standard 1-1/8"	41x30.15x7	52x40x8	33.95	49.61	28.6	39.79/30.015	12.7	13.2	126
Dive	ZS44	ZS49	standard 1-1/8"	41x30.15x7	41.8x30.5x8	44	49.61	28.6	30.015	9	2.8	142
Spin	ZS44	EC49	tapered	41x30.15x7	52x40x8	44	49.61	28.6	39.79	9	13.2	122
Astro	ZS44	ZS56	tapered/ standard 1-1/8"	41x30.15x7	52x40x8	44	55.95	28.6	39.79/30.015	9	2.8	120
Exile	ZS49	ZS49	standard 1-1/8"	41.8x30.5x8	41.8x30.5x8	49.61	49.61	28.6	30.015	9	2.8	106
Charge	EC34	EC34	standard 1-1/8"	41x30.15x7	41.8x30.5x8	33.95	33.95	28.6	30.015	12.7	13.1	99